

# FLOTATION 648

<b>TIRE SIZE</b>	<b>400/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	148 A8/144 B
<b>LI/SS FREE ROLLING</b>	160 A8/ 156 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94006328	<b>RC (IN)</b>	127.3
<b>SW (IN)</b>	15.7	<b>RIM REC</b>	AG 11.75
<b>OD (IN)</b>	42.1	<b>ECE</b>	E4-106R-002264
<b>SLR (IN)</b>	18.7	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	55	58	62
<b>5 FR</b>	12920	13320	13890
<b>10 FR</b>	11630	11980	12500
<b>20 FR</b>	10330	10660	11110
<b>25 FR</b>	9230	9510	9920
<b>30 FR</b>	8300	8560	8820
<b>5 DW</b>	9040	9330	9720
<b>10 DW</b>	8130	8390	8750
<b>20 DW</b>	7230	7450	7780
<b>25 DW</b>	6460	6660	6940
<b>30 DW</b>	5810	6000	6170

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.