


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 480/80 R 46</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STEEL BELTED SPL
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	479	<b>RIM REC</b>	DW 16 L
<b>OD (MM)</b>	1940	<b>RIM ALT</b>	DW 15 L
<b>SLR (MM)</b>	892	<b>ECE</b>	E11-106R-0010596
<b>RC (MM)</b>	5855	<b>SRI</b>	925

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
<b>70</b>	2450	2890	3330	3710	4145	4525	4965	5340	5845	6280
<b>FROM 65 TO 40</b>	2695	3175	3660	4075	4555	4970	5455	5865	6420	6900
<b>30</b>	2750	3240	3735	4155	4650	5070	5565	5985	6550	7040
<b>20</b>	2805	3305	3810	4240	4740	5170	5675	6105	6680	7180
<b>10</b>	2965	3495	4025	4480	5010	5465	6000	6455	7060	7590
<b>UPTO 30 CYC</b>	3060	3605	4155	4625	5175	5645	6190	6660	7290	7835
<b>UPTO 15 CYC</b>	3650	4305	4960	5520	6175	6735	7390	7950	8700	9350
<b>UPTO 10 CYC</b>	4000	4715	5435	6050	6765	7380	8100	8715	9535	10250
<b>10HT</b>	2750	3240	3735	4155	4650	5070	5565	5985	6550	7040

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.