

# TR 459

|                     |                  |
|---------------------|------------------|
| <b>TYRE SIZE</b>    | <b>18.4 - 28</b> |
| <b>UM</b>           | US STANDARD      |
| <b>CONSTRUCTION</b> | ⊠ BIAS           |
| <b>MACHINERY</b>    | TRACTOR          |
| <b>VERSION</b>      | INDUSTRIAL       |
| <b>TYRE TYPE</b>    | TL               |
| <b>LI/SS</b>        | 157 A8           |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94016648 | <b>RC (IN)</b> | 177.0          |
| <b>SW (IN)</b>  | 18.6     | <b>RIM REC</b> | DW 16 L        |
| <b>OD (IN)</b>  | 58.1     | <b>RIM ALT</b> | DW 15 L        |
| <b>SLR (IN)</b> | 26.1     | <b>ECE</b>     | E4-106R-002830 |

## LOAD CAPACITY (LBS/TYRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>36</b> |
| 25               | 9100      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.