


# AGRIMAX RT 600



<b>TIRE SIZE</b>	750/65 R 26
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	MIETITREBBIA / SPARGITORE / TRATTORE / ATTREZZI AGRICOLI
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	171 A8/B

## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	750	<b>RIM REC</b>	DW 24 B
<b>OD (MM)</b>	1636	<b>RIM ALT</b>	DW 23 B ; DW 25 B
<b>SLR (MM)</b>	737	<b>ECE</b>	E11-106R-006182
<b>RC (MM)</b>	4987	<b>SRI</b>	775

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.4	3.8
50	2830	3260	3690	4000	4370	4860	5230	5720	6150	-	-
40	2830	3260	3690	4000	4370	4860	5230	5720	6150	-	-
30	3030	3495	3955	4285	4680	5205	5600	6125	6585	-	-
10 LT	3795	4370	4950	5360	5855	6515	7010	7670	8245	-	-
10 HT	3030	3495	3955	4285	4680	5205	5600	6125	6585	-	-
10 CYC	-	5240	5930	6425	7015	7810	8400	9190	9880	10010	10455

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.