

PORTMAX PM 90



PORTMAX
RADIAL PORT TIRES

PORTMAX PM 90



PORTMAX PM 90 has been specially designed for reach stackers in several applications including industrial handling and steelworks. It is an All Steel radial tire that provides great durability and stability. Its special antistatic tread compound ensures particular heat resistance and an extended tire life-cycle. PORTMAX PM 90 offers reduced rolling resistance improving fuel economy.



	SIZE	US CODE	TT/TL	STAR RATING	LI/SS	RIM		O.W. (in)	OD (in)	SLR (in)	RC (in)	VERSION
						REC RIM	ALT RIM					
												
Ø25"	18.00 R 25	94045662	TL	***	207 A5	13.00/2.5	-	19.5	65.2	28.7	197.8	IND
Ø33"	18.00 R 33	94057184	TL	***	214 A5	13.00/2.50	13.00/2.50 IF	19.1	72.6	33.7	221.4	IND

IND: INDUSTRIAL

TECHNOLOGIES		PERFORMANCES	
			
A5	214 lbs		Permissible tolerances: O.O. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width O.O. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 01/08/2026