DATA SHEET

PRINTED ON
23-04-2026

EARTHMAX SR 30

TIRE SIZE	**17.5 R 25**
UM	IS STANDARD
CONSTRUCTION	RADIAL
MACHINERY	САМОСВАЛ С ЖЕСТКОЙ РАМОЙ / ПОГРУЗЧИК / ГРЕЙДЕР
VERSION	CUT RESISTANT COMPOUND
TIRE TYPE	TL
LI/SS	167 B ; 176 A2

РАЗМЕРЫ IS STANDARD

OD (MM)	1347	**TRA CODE**	E3/L3
SLR (MM)	606	**STAR RATING**	★★/★
RC (MM)	4021		
RIM REC	14.00/1.5		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	4.00	4.25	4.50	4.75	5.00	5.25
50	4375	4625	4750	5000	5150	5450
10	6000	6150	6500	6700	7100	-

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..