


FL 630 SUPER

TYRE SIZE	580/65 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRAILER / IMPLEMENTS
VERSION	STANDARD
TYRE TYPE	TL
LI/SS	174 D



DIMENSIONS US STANDARD

USA CODE	94073221	RC (IN)	159.8
SW (IN)	22.9	RIM REC	AG 18.00
OD (IN)	52.2	RIM ALT	AG 16.00; AG 17.00; AG 20.00
SLR (IN)	23.4	ECE	E11-106R-008289

LOAD CAPACITY (LBS/TYRE)

MPH / PSI	17	23	29	35	41	46	52	58	65	73	80	87
45	4310	5380	6050	7000	7940	8740	9560	10490	11170	11840	12640	13450
40	4730	5910	6650	7680	8720	9600	10490	11530	12270	13010	13890	14770
30	5730	7150	8050	9300	10550	11630	12700	13950	14850	15740	16810	17880
25	6440	8050	9050	10450	11860	13060	14270	15670	16690	17690	18890	20090
15	7470	9350	10520	12150	13780	15180	16580	18220	19380	20550	21950	23350
5	8510	10640	11970	13830	15700	17280	18880	20740	22070	23400	25000	26590

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.