

# AGRIMAX RT 657

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TIRE SIZE    | 440/65 R 24                                                                              |
| UM           | IS STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | VINEYARD HARVESTER / TRACTOR / HARVESTER                                                 |
| VERSION      | SPECIAL                                                                                  |
| TL/TT        | TL                                                                                       |
| LI/SS        | 135 D ; 138 A8                                                                           |



## DIMENSIONS IS STANDARD

|          |      |         |                |
|----------|------|---------|----------------|
| SW (MM)  | 441  | RIM REC | W 14 L         |
| OD (MM)  | 1182 | RIM ALT | W 13 ; W 15 L  |
| SLR (MM) | 538  | ECE     | E4-106R-000616 |
| RC (MM)  | 3546 | SRI     | 575            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  | 2.0  | 2.4  |
|------------|------|------|------|------|------|------|------|------|
| 65         | 1050 | 1225 | 1375 | 1530 | 1680 | 1810 | 2010 | 2180 |
| 50         | 1100 | 1285 | 1445 | 1605 | 1765 | 1905 | 2110 | 2290 |
| 40         | 1135 | 1325 | 1490 | 1655 | 1820 | 1960 | 2175 | 2360 |
| 30         | 1205 | 1410 | 1585 | 1760 | 1935 | 2085 | 2310 | 2510 |
| 10 LT      | 1405 | 1640 | 1845 | 2050 | 2255 | 2430 | 2695 | 2925 |
| 10 HT      | 1205 | 1410 | 1585 | 1760 | 1935 | 2085 | 2310 | 2510 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.