

FLOTATION 648

| | |
|---------------------------|--|
| TIRE SIZE | 500/60 - 22.5 |
| UM | IS STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | PRESSA PER BALLE DI FIENO / MIETITREBBIA / SPARGITORE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS DRIVE WHEEL | 153 A8/149 B |
| LI/SS FREE ROLLING | 165 A8/161 B |



DIMENSIONI IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 500 | RIM REC | AG 16.00 |
| OD (MM) | 1170 | RIM ALT | 15.00; 17.00 |
| SLR (MM) | 510 | ECE | E11-106R-004390 |
| RC (MM) | 3489 | PR | 18 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 3.40 | 3.50 | 3.60 |
|------------|------|------|------|
| 10 FR | 6970 | 7090 | 7210 |
| 20 FR | 6275 | 6380 | 6940 |
| 30 FR | 5580 | 5675 | 5770 |
| 40 FR | 4980 | 5065 | 5150 |
| 50 FR | 4480 | 4560 | 4625 |
| 10 DW | 4940 | 5025 | 5110 |
| 20 DW | 4450 | 4525 | 4600 |
| 30 DW | 3955 | 4020 | 4090 |
| 40 DW | 3530 | 3590 | 3650 |
| 50 DW | 3175 | 3230 | 3250 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.