

AS 504

TIRE SIZE	5.00 - 15
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TT
LI/SS DRIVE WHEEL	75 A8
LI/SS FREE ROLLING	88 A8



РАЗМЕРЫ US STANDARD

USA CODE	94019151	RC (IN)	77.0
SW (IN)	5.5	RIM REC	3.50 D
OD (IN)	25.9	RIM ALT	3.00 D; 4.00 E; 4 J
SLR (IN)	12.1	ECE	E4-106R-001950

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	51
5 FR	1730
15 FR	1470
20 FR	1380
25 FR	1230
5 DW	1190
15 DW	1010
20 DW	950
25 DW	850

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.