

# FLOTATION 648

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>700/50 - 22.5</b>  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | ⊠ BIAS  |
| <b>MACHINERY</b>          | ПРЕСС-ПОДБОРЩИК / КОМБАЙН<br>/ РАЗБРАСЫВАТЕЛЬ / КОМБАЙН /<br>СЕЛЬСКОХОЗЯЙСТВЕННОЕ<br>ОБОРУДОВАНИЕ |
| <b>VERSION</b>            | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 162 A8/158 B  |
| <b>LI/SS FREE ROLLING</b> | 174 A8/170 B  |



## РАЗМЕРЫ US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94006502 | <b>RC (IN)</b> | 148.6          |
| <b>SW (IN)</b>  | 27.6     | <b>RIM REC</b> | 24.00          |
| <b>OD (IN)</b>  | 50.0     | <b>ECE</b>     | E4-106R-001566 |
| <b>SLR (IN)</b> | 21.7     | <b>PR</b>      | 16             |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI    | 29    | 32    | 35    |
|--------------|-------|-------|-------|
| <b>5 FR</b>  | 18580 | 19640 | 20680 |
| <b>10 FR</b> | 16720 | 17680 | 18610 |
| <b>20 FR</b> | 14860 | 15720 | 16540 |
| <b>25 FR</b> | 13270 | 14030 | 14770 |
| <b>30 FR</b> | 11950 | 12630 | 13230 |
| <b>5 DW</b>  | 13180 | 13930 | 14660 |
| <b>10 DW</b> | 11860 | 12540 | 13190 |
| <b>20 DW</b> | 10540 | 11140 | 11730 |
| <b>25 DW</b> | 9410  | 9950  | 10470 |
| <b>30 DW</b> | 8480  | 8960  | 9370  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.