

# TR 461

<b>TIRE SIZE</b>	<b>15.5/80 - 18</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	LEVANTADOR TELESCÓPICO / RETROESCAVADORA
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	138 A8
<b>LI/SS FREE ROLLING</b>	150 A8



## DIMENSÕES IS STANDARD

<b>SW (MM)</b>	305	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	987	<b>RIM ALT</b>	11
<b>SLR (MM)</b>	435	<b>ECE</b>	E11-106R-006914
<b>RC (MM)</b>	2902	<b>PR</b>	18

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>5.50</b>
10 FR	4690
25 FR	3985
30 FR	3750
40 FR	3350
10 DW	3305
25 DW	2810
30 DW	2645
40 DW	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.