DATA SHEET

PRINTED ON
23-04-2026

MP 600

TYRE SIZE	**400/70 - 24**
UM	IS STANDARD
CONSTRUCTION	BIAS
MACHINERY	IMPLEMENT MACHINERY / IMPLEMENTS / UNIVERSAL VEHICLE
VERSION	STANDARD
TYRE TYPE	TL
LI/SS DRIVE WHEEL	158 A8

DIMENSIONS IS STANDARD

SW (MM)	405	**RIM REC**	13 SDC
OD (MM)	1185	**RIM ALT**	12
SLR (MM)	545	**ECE**	E11-106R-003641
RC (MM)	3530	**PR**	18

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	4.50
40 DW	4250
50 DW	4125

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..