


# AGRIMAX TERIS

**620/75 R 30 CHO**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	BIÇERDÖVER / PAMUK TOPLAMA MAKINESİ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	168 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94039586	<b>RC (IN)</b>	203.5
<b>SW (IN)</b>	24.6	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	66.6	<b>ECE</b>	E4-106R-001420
<b>SLR (IN)</b>	30.7		

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	20	23	29	35	41	46
30	5690	6550	8020	8770	9630	10490	11360	12350
25	5690	6550	8020	8770	9630	10490	11360	12350
20	6080	7010	8600	9390	10320	11240	12170	13220
10 CYC	9380	10800	13250	14470	15890	17320	18750	20370
5 CYC	10230	11780	14450	15780	17340	18890	20450	22220

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.