

AGRIMAX TURF RT 333

TIRE SIZE	280/70 R 18
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	VENDIMIADORA / MAQUINA PARA LA RECOGIDA DE FRUTA / MINITRACTOR / TRACTOR / COSECHADORA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	114 A8 ; 114 B



DIMENSIONES US STANDARD

CÓDIGO USA	94065707	RC (IN)	100.4
SW (IN)	11.4	RIM REC	W 9
OD (IN)	33.1	RIM ALT	W 8; W 10
SLR (IN)	15.4	ECE	E11-106R-006473

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1230	1420	1630	1830	2040	2240	2450	2610
25	1230	1420	1630	1830	2040	2240	2450	2610
20	1320	1520	1740	1970	2190	2410	2630	2790
5 LT	1650	1900	2180	2450	2740	3010	3290	3500
5 HT	1320	1520	1740	1970	2190	2410	2630	2790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.