

# TR 882

<b>TIRE SIZE</b>	<b>400/60 - 15.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	PRESSE À PAILLE / MOISSONNEUSE / OUTILLAGE AGRICOLE / REMORQUE / MOISSONNEUSE / OUTILLAGE AGRICOLE / REMORQUE
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	132 A8
<b>LI/SS FREE ROLLING</b>	145 A8



## DIMENSIONS US STANDARD

<b>CODE USA</b>	94034529	<b>RC (IN)</b>	102.6
<b>SW (IN)</b>	15.7	<b>RIM REC</b>	AG 13.00
<b>OD (IN)</b>	34.4	<b>ECE</b>	E4-106R-001879
<b>SLR (IN)</b>	14.9	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	52
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390
5 DW	6170
15 DW	5250
20 DW	4940
25 DW	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.