


AGRIMAX RT 945

| | |
|---------------------|--|
| TIRE SIZE | 320/90 R 46 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 148 D ; 151 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 319 | RIM REC | W 10 |
| OD (MM) | 1744 | RIM ALT | W 9; W 11 |
| SLR (MM) | 810 | ECE | E11-106R-004068 |
| RC (MM) | 5232 | SRI | 825 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 | 3.6 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 1355 | 1765 | 2145 | 2365 | 2490 | 2745 | 2965 | 3150 |
| 50 | 1425 | 1855 | 2255 | 2485 | 2615 | 2880 | 3115 | 3310 |
| 40 | 1485 | 1935 | 2350 | 2590 | 2730 | 3005 | 3245 | 3450 |
| 30 | 1560 | 2030 | 2465 | 2715 | 2860 | 3150 | 3405 | 3620 |
| 10 | 2035 | 2650 | 3215 | 3545 | 3735 | 4115 | 4445 | 4725 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.