


AGRIMAX RT 955

TIRE SIZE	270/80 R 36
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	FELDSPRITZE / TRAUBENERNTEMASCHINE / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	134 A8/B



ABMESSUNGEN US STANDARD

USA-CODE	94067046	RC (IN)	161.0
SW (IN)	10.8	RIM REC	W9
OD (IN)	53.0	RIM ALT	W8; W10
SLR (IN)	24.8	ECE	E11-106R-006758

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52	58
30	1640	1920	2200	2480	2770	3000	3330	3510	3840	4170	4440	4670
25	1640	1920	2200	2480	2770	3000	3330	3510	3840	4170	4440	4670
20	1750	2060	2360	2660	2950	3210	3560	3760	4110	4460	4760	5000
5	2460	2880	3300	3730	4140	4500	4980	5260	5750	6250	6670	7010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.