


# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>340/85 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	SPECIAL
<b>TL/TT</b>	TL
<b>LI/SS</b>	127 A8/B



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94044252	<b>RC (IN)</b>	153.1
<b>SW (IN)</b>	13.9	<b>RIM REC</b>	W 12
<b>OD (IN)</b>	50.7	<b>RIM ALT</b>	W 11
<b>SLR (IN)</b>	23.1	<b>ECE</b>	E4-106R-000593

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	2130	2470	2820	3160	3520	3860
25	2130	2470	2820	3160	3520	3860
20	2280	2650	3020	3390	3770	4130
5 LT	2840	3320	3780	4240	4710	5170
5 HT	2280	2650	3020	3390	3770	4130

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.