


# AGRIMAX RT 855

<b>TYRE SIZE</b>	<b>210/95 R 16</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	106 A8/B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	214	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	806	<b>RIM ALT</b>	W 6 ; 6 LB
<b>SLR (MM)</b>	360	<b>ECE</b>	E4-106R-000608
<b>RC (MM)</b>	2387	<b>SRI</b>	370

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	450	515	590	665	745	820	885	950
40	450	515	590	665	745	820	885	950
30	480	555	635	715	800	880	950	1020
10 LT	600	690	795	895	995	1100	1190	1275
10 HT	480	555	635	715	800	880	950	1020

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.