

# AW 702

<b>TIRE SIZE</b>	<b>10.0/75 - 15.3</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ENFARDADEIRA DE FENO / IMPLEMENTOS AGRÍCOLAS / REBOQUE / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS / REBOQUE
<b>VERSÃO</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	135 A8



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94048472	<b>RC (IN)</b>	87.1
<b>SW (IN)</b>	10.8	<b>RIM REC</b>	9.00
<b>OD (IN)</b>	29.9	<b>ECE</b>	E11-106R-005317
<b>SLR (IN)</b>	13.8	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>103</b>
<b>5 FR</b>	6720
<b>15 FR</b>	5720
<b>20 FR</b>	5380
<b>25 FR</b>	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.