


MULTIMAX MP 522

| | |
|---------------------|--|
| TIRE SIZE | 440/80 R 28 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 156 A8/B |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|---------------------------|
| SW (MM) | 441 | RIM REC | DW 14 L |
| OD (MM) | 1415 | RIM ALT | DW 13 ; DW 13 L ; DW 15 L |
| SLR (MM) | 643 | ECE | E11-106R-002968 |
| RC (MM) | 4278 | SRI | 675 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6 | 2.0 | 2.2 | 2.4 | 2.6 | 2.8 | 3.0 | 3.2 | 3.4 | 3.6 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 50 | 2300 | 2725 | 2940 | 3150 | 3360 | 3575 | 3790 | 4000 | - | - |
| 40 | 2300 | 2725 | 2940 | 3150 | 3360 | 3575 | 3790 | 4000 | - | - |
| 30 | 2480 | 2930 | 3155 | 3380 | 3605 | 3830 | 4055 | 4280 | - | - |
| 25 | 2570 | 3040 | 3270 | 3505 | 3740 | 3970 | 4205 | 4440 | - | - |
| 10 CYC. | 2840 | 3470 | 3790 | 4105 | 4420 | 4735 | 5050 | 5370 | 5685 | 6000 |
| STATIC | 4360 | 5330 | 5810 | 6295 | 6780 | 7265 | 7750 | 8230 | 8715 | 9200 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.