

AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 210/95 R 18 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / VINDIMADORA / TRATOR / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 108 A8/B |



DIMENSÕES US STANDARD

| | | | |
|-------------------|----------|----------------|---------------|
| CÓDIGO USA | 94028672 | RC (IN) | 101.0 |
| SW (IN) | 8.4 | RIM REC | W 7 |
| OD (IN) | 33.7 | RIM ALT | W 6 |
| SLR (IN) | 15.2 | ECE | E4-106R-00634 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-------------|------|------|------|------|------|------|------|------|
| 30 | 1040 | 1190 | 1370 | 1540 | 1720 | 1900 | 2050 | 2210 |
| 25 | 1040 | 1190 | 1370 | 1540 | 1720 | 1900 | 2050 | 2210 |
| 20 | 1110 | 1280 | 1470 | 1650 | 1840 | 2040 | 2200 | 2360 |
| 5 LT | 1390 | 1600 | 1840 | 2070 | 2310 | 2550 | 2760 | 2950 |
| 5 HT | 1110 | 1280 | 1470 | 1650 | 1840 | 2040 | 2200 | 2360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.