

# AS 504

<b>TIRE SIZE</b>	<b>27X10 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊗ BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	95 A8
<b>LI/SS FREE ROLLING</b>	107 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	260	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	695	<b>ECE</b>	E4-106R-002324
<b>SLR (MM)</b>	317	<b>PR</b>	8
<b>RC (MM)</b>	2071		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.10
10 FR	1365
25 FR	1160
30 FR	1090
40 FR	975
10 DW	965
25 DW	820
30 DW	775
40 DW	690

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.