


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 540/65 R 30</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTEUR DE FORTE PUISSANCE / TRACTEUR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	158 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	549	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1464	<b>RIM ALT</b>	DW 18 L
<b>SLR (MM)</b>	650	<b>ECE</b>	E11-106R-005711
<b>RC (MM)</b>	4351	<b>SRI</b>	700

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	1970	2275	2585	2935	3205	3480	3865
FROM 65 TO 40	2165	2505	2845	3230	3525	3825	4250
30	2205	2555	2900	3290	3595	3900	4335
20	2250	2605	2955	3355	3665	3975	4420
10	2380	2755	3125	3550	3875	4205	4675
*UPTO 10 CYC WITH FRONT LOADER	3030	3505	3980	4520	4935	5355	5950
10HT	2205	2555	2900	3290	3595	3900	4335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.