

# FLOTATION 648

	<b>550/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALYA MAKINESİ / BIÇERDÖVER / YAYICI / BIÇERDÖVER / UYGULAMALI MAKINE
<b>VERSION</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
	158 A8/154 B
	171 A8/167 B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94044474	<b>RC (IN)</b>	146.7
<b>SW (IN)</b>	21.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	48.8	<b>ECE</b>	E11-106R-004391
<b>SLR (IN)</b>	21.3	<b>PR</b>	20

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	48	49	51
5 FR	18330	18660	18980
10 FR	16500	16790	17080
20 FR	14670	14920	15190
25 FR	13090	13330	13560
30 FR	11780	11990	12010
5 DW	12660	12900	13120
10 DW	11400	11610	11810
20 DW	10140	10320	10490
25 DW	9050	9210	9370
30 DW	7990	8120	8270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.