

## AT 171



# AT 171



AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.



|      | SIZE      | LI/SS         | RIM                                                                               |                                                                                   | SW<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | SRI<br>index | VERSION |
|------|-----------|---------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------|------------|-------------|------------|--------------|---------|
|      |           |               | REC RIM                                                                           | ALT RIM                                                                           |            |            |             |            |              |         |
|      |           |               |  |  |            |            |             |            |              |         |
| Ø14" | 30X9 -14  | 77 A8<br>53 F | W 7                                                                               | W 6                                                                               | 211        | 755        | 0           | 0          | -            | STD     |
|      | 28X9 -14  | 77 A8<br>53 F | W 7                                                                               | W 6                                                                               | 205        | 715        | 0           | 0          | -            | STD     |
| Ø16" | 31X9 -16  | 80 A8<br>56 F | W 7                                                                               | W 6                                                                               | 211        | 785        | 0           | 0          | -            | STD     |
| Ø18" | 35X10 -18 | 90 A8<br>66 F | W 8                                                                               | -                                                                                 | 241        | 900        | 417         | 2646       | -            | STD     |
|      | 33X8 -18  | 83 A8<br>59 F | W 6                                                                               | W 5.5                                                                             | 200        | 845        | 390         | 2525       | -            | STD     |

STD: STANDARD

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|  |  |  | Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index |
|  |  |                                                                                     |                                                                                                                                                                                  |
| F                                                                                   | 95 kg                                                                               |                                                                                     |                                                                                                                                                                                  |

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

|      | SIZE      | LI/SS         | RIM                                                                               |                                                                                   | SW<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | SRI<br>index | VERSION |
|------|-----------|---------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------|------------|-------------|------------|--------------|---------|
|      |           |               | REC RIM                                                                           | ALT RIM                                                                           |            |            |             |            |              |         |
|      |           |               |  |  |            |            |             |            |              |         |
|      | 35X10 -18 | 90 A8<br>66 F | W 8                                                                               | -                                                                                 | 241        | 900        | 417         | 2646       | -            | STD     |
| Ø20" | 38X10 -20 | 93 A8<br>69 F | W 8                                                                               | W 7                                                                               | 235        | 950        | 442         | 2835       | -            | STD     |
|      | 35X9 -20  | 85 A8<br>61 F | W 7                                                                               | W 6                                                                               | 200        | 895        | 419         | 2670       | -            | STD     |
|      | 35X9 -20  | 85 A8<br>61 F | W 7                                                                               | W 6                                                                               | 200        | 895        | 419         | 2670       | -            | STD     |
|      | 38X10 -20 | 93 A8<br>69 F | W 8                                                                               | W 7                                                                               | 235        | 950        | 442         | 2835       | -            | STD     |
|      | 33X9 -20  | 85 A8<br>61 F | W 7                                                                               | W 6                                                                               | 205        | 838        | 387         | 2616       | -            | STD     |
|      |           |               |                                                                                   |                                                                                   |            |            |             |            |              |         |
| Ø22" | 37X9 -22  | 88 A8<br>64 F | W 7                                                                               | W 6                                                                               | 205        | 945        | 444         | 2778       | -            | STD     |
|      | 40X10 -22 | 95 A8<br>71 F | W 8                                                                               | W 7                                                                               | 235        | 1005       | 469         | 2955       | -            | STD     |
|      | 40X10 -22 | 95 A8<br>71 F | W 8                                                                               | W 7                                                                               | 235        | 1005       | 469         | 2955       | 0            | STD     |
|      | 35X9 -22  | 88 A8<br>64 F | W7                                                                                | W6                                                                                | 210        | 890        | 0           | 0          | -            | STD     |

STD: STANDARD

| TECHNOLOGIES                                                                             |                                                                                              | PERFORMANCES                                                                        |                                                                                                                                                                                  |
|------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
|       | <br>R1W+  |  | Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index |
| <br>F | <br>95 kg |                                                                                     |                                                                                                                                                                                  |

| SIZE     | LI/SS         | RIM                                                                               |                                                                                   | SW<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | SRI<br>index | VERSION |     |
|----------|---------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------|------------|-------------|------------|--------------|---------|-----|
|          |               | REC RIM                                                                           | ALT RIM                                                                           |            |            |             |            |              |         |     |
|          |               |  |  |            |            |             |            |              |         |     |
| 37X9 -22 | 88 A8<br>64 F | W 7                                                                               | W 6                                                                               | 205        | 945        | 444         | 2778       | -            | STD     |     |
| Ø24"     | 40X9 -24      | 90 A8<br>66 F                                                                     | W 7                                                                               | W 6        | 211        | 995         | 462        | 3112         | -       | STD |

STD: STANDARD

| TECHNOLOGIES                                                                                       |                                                                                                 | PERFORMANCES                                                                                        |                                                                                     |
|----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
| <br><b>R1W+</b> | <br><b>F</b> | <br><b>95 kg</b> |  |
|                                                                                                    |                                                                                                 |                                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index