


# AGRIMAX TERIS

<b>TYRE SIZE</b>	<b>1050/50 R 32 CHO</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	184 A8 ; 181 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	1059	<b>RIM REC</b>	36.0 VA (multipiece)
<b>OD (MM)</b>	1893	<b>ECE</b>	E4-106R-000813
<b>SLR (MM)</b>	840	<b>SRI</b>	875
<b>RC (MM)</b>	5685		

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.8	1.0	1.4	1.6	2.0	2.4	2.8	3.2
50	3715	4210	5280	5860	6520	7015	7675	8250
40	4050	4590	5760	6390	7110	7650	8370	9000
30	4335	4915	6165	6840	7610	8190	8960	9630
15 CYC	6685	7575	9505	10545	11735	12625	13815	14850
10 CYC	7290	8265	10370	11505	12800	13770	15070	16200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.