


# AGRIMAX V- FLECTO



<b>TIRE SIZE</b>	<b>VF 600/60 R 28</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATOR DE ALTA POTENCIA / TRATOR
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	157 D

## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94058495	<b>RC (IN)</b>	166.5
<b>SW (IN)</b>	23.1	<b>RIM REC</b>	DW 20 B
<b>OD (IN)</b>	56.7	<b>RIM ALT</b>	DW 18 L
<b>SLR (IN)</b>	24.9	<b>ECE</b>	E11-106R-004471

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	4540	5290	6030	6780	7520	8270
<b>FROM 40 TO 25</b>	4990	5820	6640	7450	8270	9095
20	5090	5930	6770	7590	8430	9270
12	5190	6050	6900	7750	8600	9460
5	5490	6390	7300	8190	9090	10000
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	6990	8150	9280	10430	11570	12730
5 HT	5090	5930	6770	7590	8430	9270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.