


TRAC SUPER

| | |
|---------------------|--|
| TIRE SIZE | 440/50 R 17 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MINITRACTOR / TRACTOR |
| VERSIÓN | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 135 D |



DIMENSIONES US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CÓDIGO USA | 94038534 | RC (IN) | 105.3 |
| SW (IN) | 17.4 | RIM REC | 14.00 |
| OD (IN) | 34.3 | RIM ALT | 13.00 |
| SLR (IN) | 15.6 | ECE | E4-106R-000662 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12 | 15 | 17 | 23 | 29 | 35 | 41 | 46 | 52 |
|-----------|------|------|------|------|------|------|------|------|------|
| 40 | 2110 | 2120 | 2360 | 2790 | 3170 | 3600 | 4090 | 4380 | 4810 |
| 25 | 2870 | 2880 | 3210 | 3790 | 4320 | 4910 | 5570 | 5950 | 6540 |
| 20 | 3170 | 3200 | 3560 | 4220 | 4790 | 5460 | 6180 | 6610 | 7260 |
| 5 | 3790 | 3810 | 4240 | 5030 | 5720 | 6490 | 7360 | 7880 | 8650 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.