


AGRIMAX TERIS

TIRE SIZE	710/55 R 28 CHO
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	КОМБАЙН / ХЛОПКОУБОРОЧНАЯ МАШИНА
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	164 A8/B



РАЗМЕРЫ US STANDARD

USA CODE	94060023	RC (IN)	174.9
SW (IN)	28.2	RIM REC	DW 23 B
OD (IN)	58.8	ECE	E11-106R-005940
SLR (IN)	26.1		

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46
30	4300	4960	5620	6390	7050	7830	8710	9370	10250	11020
25	4300	4960	5620	6390	7050	7830	8710	9370	10250	11020
20	4610	5310	6020	6840	7550	8380	9330	10030	10980	11790
10 CYC	7100	8190	9280	10550	11640	12920	14370	15460	16920	18190
5 CYC	7740	8930	10120	11510	12700	14090	15670	16860	18450	19840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.