


# EARTHMAX SR 22



|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>23.5 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | NIVELEUSE / CHARGEUR / BULLDOZER<br>/ CHARGEUR / BULLDOZER /<br>NIVELEUSE                |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 170 A8 ; 195 A2  |

## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>CODE USA</b> | 94062911 | <b>RIM REC</b>     | 19.50/2.5 |
| <b>OD (IN)</b>  | 63.5     | <b>TRA CODE</b>    | G2/L2     |
| <b>SLR (IN)</b> | 27.9     | <b>STAR RATING</b> | ★         |
| <b>RC (IN)</b>  | 191.5    |                    |           |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 18   | 22   | 25   | 29   | 33    | 36    | 40    | 44    | 58    | 62    | 65    | 69    | 73    |
|-----------|------|------|------|------|-------|-------|-------|-------|-------|-------|-------|-------|-------|
| 25        | 6950 | 7850 | 8800 | 9900 | 10700 | 11700 | 12300 | 13200 | -     | -     | -     | -     | -     |
| 5         | -    | -    | -    | -    | -     | -     | -     | -     | 22700 | 23400 | 24700 | 25400 | 26800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.