

# FLOTATION 648

<b>TIRE SIZE</b>	<b>600/50 - 22.5</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	DUAL BEAD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	156 A8/152 B
<b>LI/SS FREE ROLLING</b>	169 A8/165 B



## DIMENSIONER IS STANDARD

<b>SW (MM)</b>	611	<b>RIM REC</b>	AG 20.00
<b>OD (MM)</b>	1170	<b>ECE</b>	E11-106R-004392
<b>SLR (MM)</b>	510	<b>PR</b>	20
<b>RC (MM)</b>	3501		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.00	3.10	3.20
10 FR	7820	7975	8120
20 FR	7035	7175	7310
30 FR	6255	6380	6495
40 FR	5585	5695	5800
50 FR	5025	5125	5150
10 DW	5390	5495	5600
20 DW	4850	4945	5040
30 DW	4310	4395	4480
40 DW	3850	3925	4000
50 DW	3465	3535	3550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.