


# AGRIMAX ELOS

<b>TIRE SIZE</b>	<b>520/85 R 42</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	167 A8/B



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94075850	<b>RC (IN)</b>	240.0
<b>SW (IN)</b>	20.3	<b>RIM REC</b>	DW 16 L
<b>OD (IN)</b>	78.3	<b>RIM ALT</b>	DD 18 L; DW 18 L
<b>SLR (IN)</b>	36.2	<b>ECE</b>	E11-106R-0010146

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	14	17	20	23	29	35	41	46	52	58
<b>30</b>	4700	5530	6370	7100	7940	8650	9500	10460	11300	12010
<b>25</b>	4700	5530	6370	7100	7940	8650	9500	10460	11300	12010
<b>20</b>	5030	5920	6820	7590	8500	9270	10160	11200	12090	12860
<b>5 LT</b>	6280	7420	8540	9500	10640	11600	12730	14020	15140	16100
<b>5 HT</b>	5030	5920	6820	7590	8500	9270	10160	11200	12090	12860

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.