

# AS 504

<b>TIRE SIZE</b>	<b>11.5/80 - 15.3</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	SOLLEVATORE TELESOPICO / RIMORCHIO DA CAMPO / ATTREZZI AGRICOLI / SOLLEVATORE TELESOPICO
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS DRIVE WHEEL</b>	123 A8
<b>LI/SS FREE ROLLING</b>	135 A8



## DIMENSIONI IS STANDARD

<b>SW (MM)</b>	290	<b>RIM REC</b>	9.00
<b>OD (MM)</b>	867	<b>ECE</b>	E4-106R-001894
<b>SLR (MM)</b>	380	<b>PR</b>	12
<b>RC (MM)</b>	2540	<b>SRI</b>	410

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>4.10</b>
10 FR	3050
25 FR	2595
30 FR	2440
40 FR	2180
10 DW	2170
25 DW	1845
30 DW	1735
40 DW	1550

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.