

# TR 128

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | 7 - 14  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> | BIAS  |
| <b>MACHINERY</b>    | CULTIVADOR ROTATIVO / VEICULO<br>UNIVERSAL / IMPLEMENTOS<br>AGRÍCOLAS |
| <b>VERSÃO</b>       | STANDARD  |
| <b>TIRE TYPE</b>    | TT  |
| <b>LI/SS</b>        | 95 A6   |



## DIMENSÕES IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 173  | <b>RIM REC</b> | 5 JA            |
| <b>OD (MM)</b>  | 690  | <b>RIM ALT</b> | 5 J             |
| <b>SLR (MM)</b> | 323  | <b>ECE</b>     | E11-106R-004093 |
| <b>RC (MM)</b>  | 2086 | <b>PR</b>      | 8               |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>4.00</b> |
| 30                | 685         |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.