


# EARTHMAX SR 53

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>17.5 R 25</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | DOZER / LOADER   |
| <b>VERSION</b>      | CUT RESISTANT COMPOUND   |
| <b>TYRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 182 A2   |



## DIMENSIONS US STANDARD

|                 |          |                    |           |
|-----------------|----------|--------------------|-----------|
| <b>USA CODE</b> | 94058945 | <b>RIM REC</b>     | 14.00/1.5 |
| <b>OD (IN)</b>  | 55.1     | <b>TRA CODE</b>    | L5        |
| <b>SLR (IN)</b> | 25.1     | <b>STAR RATING</b> | ★★        |
| <b>RC (IN)</b>  | 165.9    |                    |           |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 76    | 80    | 83    | 87    | 91    | 94    |
|-----------|-------|-------|-------|-------|-------|-------|
| 5         | 16100 | 16500 | 17100 | 17600 | 18200 | 18700 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.