

# AGRIMAX V-FLECTO



|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | VF 650/85 R 42 CFO                                                                       |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | HIGH-POWER TRACTOR / TRACTOR                                                             |
| VERSION      | SPECIAL                                                                                  |
| TL/TT        | TL                                                                                       |
| LI/SS        | 183 D                                                                                    |

## DIMENSIONS US STANDARD

|          |          |         |                  |
|----------|----------|---------|------------------|
| USA CODE | 94515875 | RC (IN) | 252.5            |
| SW (IN)  | 26.8     | RIM REC | DW 23 B          |
| OD (IN)  | 85.0     | RIM ALT | DW20B;DW21B      |
| SLR (IN) | 36.9     | ECE     | E11-106R-0011307 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI     | 9     | 12    | 15    | 17    | 20    | 23    | 29    |
|---------------|-------|-------|-------|-------|-------|-------|-------|
| 45            | 8770  | 10170 | 11570 | 13160 | 14560 | 15960 | 17550 |
| FROM 40 TO 25 | 9640  | 11190 | 12730 | 14460 | 16000 | 17550 | 19290 |
| 20            | 9830  | 11410 | 12980 | 14750 | 16320 | 17900 | 19680 |
| 12            | 10030 | 11630 | 13240 | 15050 | 16640 | 18250 | 20060 |
| 5             | 10600 | 12300 | 14000 | 15910 | 17600 | 19300 | 21220 |
| UPTO 20 CYC   | 10950 | 12690 | 14440 | 16410 | 18170 | 19920 | 21890 |
| UPTO 10 CYC   | 13060 | 15160 | 17240 | 19600 | 21680 | 23780 | 26130 |
| UPTO 5CYC     | 14320 | 16600 | 18890 | 21470 | 23760 | 26060 | 28640 |
| 5 HT          | 9830  | 11410 | 12980 | 14750 | 16320 | 17900 | 19680 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.