


AGRIMAXFACTOR

| | |
|---------------------|--|
| TIRE SIZE | 710/70 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ТРАКТОР-ТЯГАЧ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 175 D ; 178 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|-----------------|-----------------|
| SW (MM) | 716 | RIM REC | DW 23 B |
| OD (MM) | 1959 | ECE | E11-106R-007638 |
| SLR (MM) | 866 | SRI | 925 |
| RC (MM) | 5800 | TRA CODE | R1W |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|------|------|------|------|
| 65 | 2695 | 3175 | 3660 | 4075 | 4555 | 4970 | 5455 | 5865 | 6420 | 6900 |
| 50 | 2830 | 3335 | 3840 | 4275 | 4785 | 5220 | 5725 | 6160 | 6740 | 7245 |
| 40 | 2925 | 3450 | 3975 | 4425 | 4950 | 5400 | 5925 | 6375 | 6975 | 7500 |
| 30 | 3095 | 3655 | 4210 | 4685 | 5240 | 5715 | 6270 | 6745 | 7380 | 7935 |
| 10 LT | 3610 | 4255 | 4905 | 5460 | 6105 | 6660 | 7310 | 7865 | 8605 | 9250 |
| 10 HT | 3095 | 3655 | 4210 | 4685 | 5240 | 5715 | 6270 | 6745 | 7380 | 7935 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.