

# FLOTATION 558

<b>TYRE SIZE</b>	500/45 - 22.5
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	HAY HARVESTER / TRAILER / IMPLEMENTS
<b>VERSION</b>	ARAMID BELTED HD
<b>TYRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	142 A8/138 B
<b>LI/SS FREE ROLLING</b>	154 A8/150 B



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	500	<b>RIM REC</b>	AG 16.00
<b>OD (MM)</b>	1045	<b>ECE</b>	E11-106R-005352
<b>SLR (MM)</b>	471	<b>PR</b>	16
<b>RC (MM)</b>	3167		

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	3.20	3.40	3.60
10 FR	4900	5075	5250
20 FR	4410	4570	4725
30 FR	3920	4060	4200
40 FR	3500	3625	3750
50 FR	3150	3265	3350
10 DW	3465	3590	3710
20 DW	3120	3230	3340
30 DW	2770	2875	2970
40 DW	2475	2565	2650
50 DW	2230	2310	2360

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.