

AS 504

| | |
|---------------------------|--|
| TIRE SIZE | 7.50 - 18 |
| UM | US STANDARD |
| CONSTRUCTION | ⊠ BIAS |
| MACHINERY | ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК |
| VERSION | STANDARD |
| TIRE TYPE | TT |
| LI/SS DRIVE WHEEL | 111 A8 |
| LI/SS FREE ROLLING | 122 A8 |



РАЗМЕРЫ US STANDARD

| | | | |
|-----------------|----------|----------------|------------------------|
| USA CODE | 94065394 | RC (IN) | 104.3 |
| SW (IN) | 8.2 | RIM REC | 5.50 F |
| OD (IN) | 33.6 | RIM ALT | 4.50 E; 6.00 F; 5.00 F |
| SLR (IN) | 16.0 | ECE | E11-106R-006456 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 74 |
|-----------|------|
| 5 FR | 4630 |
| 15 FR | 3935 |
| 20 FR | 3700 |
| 25 FR | 3300 |
| 5 DW | 3360 |
| 15 DW | 2855 |
| 20 DW | 2690 |
| 25 DW | 2400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.