

FLOTATION 558

| | |
|---------------------|--|
| | 400/55 - 22.5 |
| UM | US STANDARD |
| CONSTRUCTION | BIAS |
| MACHINERY | BALYA MAKINESI / BIÇERDÖVER / TANKER / RÖMORK / BIÇERDÖVER / UYGULAMALI MAKINE |
| VERSION | ARAMID BELTED HD |
| TIRE TYPE | TL |
| | 140 A8/136 B |
| | 152 A8/148 B |



UNDEFINED US STANDARD

| | | | |
|-----------------|----------|----------------|------------------------|
| USA CODE | 94048298 | RC (IN) | 121.4 |
| SW (IN) | 15.9 | RIM REC | AG 11.75 |
| OD (IN) | 40.2 | RIM ALT | 12.25; 13.00; AG 13.00 |
| SLR (IN) | 17.5 | ECE | E11-106R-005350 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 54 | 55 | 58 |
|-----------|-------|-------|-------|
| 5 FR | 10460 | 10640 | 10960 |
| 10 FR | 9410 | 9570 | 9870 |
| 20 FR | 8370 | 8510 | 8760 |
| 25 FR | 7470 | 7590 | 7830 |
| 30 FR | 6720 | 6830 | 6940 |
| 5 DW | 7370 | 7480 | 7720 |
| 10 DW | 6640 | 6730 | 6940 |
| 20 DW | 5900 | 5990 | 6170 |
| 25 DW | 5270 | 5350 | 5510 |
| 30 DW | 4740 | 4820 | 4940 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.