


# RIDEMAX FL 693 M



<b>TIRE SIZE</b>	<b>600/60 R 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TANKBIL / SLÄPVAGN / ARBETSFORDON
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	169 D

## DIMENSIONER US STANDARD

<b>USA CODE</b>	94064335	<b>RC (IN)</b>	177.0
<b>SW (IN)</b>	23.8	<b>RIM REC</b>	AG 20.00
<b>OD (IN)</b>	58.9	<b>RIM ALT</b>	AG 18.00
<b>SLR (IN)</b>	26.8	<b>ECE</b>	E11-106R-006160

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	15	17	23	29	35	41	46	52	58
45	4250	4770	5940	6760	7800	8850	9670	10590	11640
40	4670	5250	6530	7420	8580	9720	10610	11640	12790
30	5650	6350	7900	8980	10370	11770	12850	14090	15480
25	6350	7130	8870	10100	11660	13230	14440	15830	17390
20	7050	7930	9850	11210	12940	14680	16040	17580	19310
15	7390	8290	10310	11730	13550	15370	16780	18400	20200
5	8410	9450	11740	13360	15420	17490	19110	20950	23010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.