

# TR 135

|                     |                      |
|---------------------|----------------------|
| <b>TIRE SIZE</b>    | 12.4 - 36            |
| <b>UM</b>           | IS STANDARD          |
| <b>CONSTRUCTION</b> | ⊠ BIAS               |
| <b>MACHINERY</b>    | TRATTORE / RIMORCHIO |
| <b>VERSIONE</b>     | HD                   |
| <b>TIRE TYPE</b>    | TT                   |
| <b>LI/SS</b>        | 135 A6               |



## DIMENSIONI IS STANDARD

|                 |      |                |           |
|-----------------|------|----------------|-----------|
| <b>SW (MM)</b>  | 325  | <b>RIM REC</b> | W 11      |
| <b>OD (MM)</b>  | 1465 | <b>RIM ALT</b> | W 9; W 10 |
| <b>SLR (MM)</b> | 687  | <b>PR</b>      | 12        |
| <b>RC (MM)</b>  | 4558 | <b>SRI</b>     | 700       |

## LOAD CAPACITY (KG/TIRE)

|                   |             |
|-------------------|-------------|
| <b>KM/H / BAR</b> | <b>3.50</b> |
| 30                | 2180        |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.