


# AW 09

<b>TIRE SIZE</b>	<b>380/55 - 17</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	HEUPRESSE / LANDWIRTSCHAFTLICHE GERÄTE / ANHÄNGER / ERNTEMASCHINE / LANDWIRTSCHAFTLICHE GERÄTE / ERNTEMASCHINE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	128 A8
<b>LI/SS FREE ROLLING</b>	141 A8



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	390	<b>RIM REC</b>	13.00
<b>OD (MM)</b>	850	<b>ECE</b>	E4-106R-000380
<b>SLR (MM)</b>	377		
<b>RC (MM)</b>	2491		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.20
10 FR	3605
25 FR	3065
30 FR	2885
40 FR	2575
10 DW	2520
25 DW	2140
30 DW	2015
40 DW	1800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.