

# AGRIMAX V- FLECTO

**VF 710/60 R 38**

<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	YÜKSEK GÜÇTE TRAKTÖR / TRAKTÖR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
	171 D



## UNDEFINED US STANDARD

<b>USA CODE</b>	94058563	<b>RC (IN)</b>	214.4
<b>SW (IN)</b>	27.9	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	71.7	<b>RIM ALT</b>	DW 23 B
<b>SLR (IN)</b>	31.3	<b>ECE</b>	E11-106R-004520

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
45	6780	7890	8990	10110	11220	12330
<b>FROM 40 TO 25</b>	7450	8670	9890	11110	12330	13560
20	7590	8840	10070	11330	12580	13820
12	7750	9020	10270	11550	12820	14100
5	8190	9530	10870	12210	13560	14910
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	10430	12140	13830	15550	17260	18980
5 HT	7590	8840	10070	11330	12580	13820

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.