


# AGRIMAX SPARGO

TIRE SIZE	VF 480/95 R 54
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	TRACTEUR
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	180 D



## DIMENSIONS IS STANDARD

SW (MM)	509	RIM REC	DW 16 L
OD (MM)	2300	RIM ALT	DW 15 L
SLR (MM)	1033	ECE	E11-106R-0011499
RC (MM)	6956	SRI	1075

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.8
70	4220	4735	5255	5770	6065	6360	6545	6730	7395
FROM 65 TO 40	4560	5120	5680	6240	6560	6880	7080	7280	8000
30	4655	5225	5795	6365	6695	7020	7225	7430	8160
20	4745	5325	5910	6490	6825	7160	7365	7575	8320
10	5020	5635	6250	6865	7220	7570	7790	8010	8800
UPTO 15 CYC.	6180	6940	7700	8460	8890	9325	9595	9865	10840
UPTO 30 CYC.	5180	5815	6450	7085	7450	7810	8040	8265	9080

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.