

RIDEMAX FROST

| | |
|---------------------|------------------------|
| TIRE SIZE | 440/80 R 24 IND |
| UM | IS STANDARD |
| CONSTRUCTION | |
| MACHINERY | TRACTOR |
| VERSION | STEEL BELTED |
| TL/TT | TL |
| LI/SS | 154 A8 ; 149 D |



DIMENSIONS IS STANDARD

| | | | |
|-----------------|------|----------------|------------------|
| SW (MM) | 441 | RIM REC | DW 14 L |
| OD (MM) | 1314 | RIM ALT | DW 15 L |
| SLR (MM) | 597 | ECE | E11-106R-0011765 |
| RC (MM) | 3984 | SRI | 625 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.8 | 1.2 | 1.6 | 2 | 2.4 | 2.6 | 2.8 | 3 | 3.2 |
|------------|------|------|------|------|------|------|------|------|------|
| 65 | 1495 | 1920 | 2340 | 2570 | 2765 | 2895 | 3025 | 3155 | 3250 |
| 50 | 1615 | 2075 | 2530 | 2775 | 2985 | 3125 | 3265 | 3405 | 3510 |
| 40 | 1725 | 2210 | 2695 | 2955 | 3180 | 3330 | 3480 | 3630 | 3750 |
| 30 | 1795 | 2305 | 2810 | 3085 | 3315 | 3475 | 3630 | 3785 | 3900 |
| 20 | 1885 | 2420 | 2950 | 3240 | 3485 | 3645 | 3810 | 3975 | 4095 |
| 10 | 2155 | 2765 | 3370 | 3700 | 3980 | 4170 | 4355 | 4540 | 4680 |
| 5 | 2500 | 3205 | 3910 | 4290 | 4620 | 4835 | 5050 | 5270 | 5430 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.