


AGRIMAX FORCE



| | |
|---------------------|--|
| TIRE SIZE | IF 800/70 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | MAȘINĂ DE RECOLTARE / TRACTOR DE MARE PUTERE / TRACTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 184 D |

DIMENSIUNI IS STANDARD

| | | | |
|-----------------|------|----------------|---------------------------|
| SW (MM) | 794 | RIM REC | DW 27 B |
| OD (MM) | 2085 | RIM ALT | DW 25 B; DW 28 B; DW 30 B |
| SLR (MM) | 923 | ECE | E11-106R-006497 |
| RC (MM) | 6184 | SRI | 975 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|----------------------|------|------|------|-------|-------|-------|-------|-------|
| 70 | 3845 | 4500 | 5155 | 5730 | 6305 | 6795 | 7615 | 8190 |
| FROM 65 TO 40 | 4230 | 4950 | 5670 | 6300 | 6930 | 7470 | 8370 | 9000 |
| 30 | 4395 | 5145 | 5895 | 6550 | 7205 | 7765 | 8700 | 9360 |
| 20 | 4565 | 5345 | 6120 | 6800 | 7480 | 8065 | 9035 | 9720 |
| 10 | 5370 | 6285 | 7200 | 8000 | 8800 | 9485 | 10625 | 11430 |
| UPTO 30 CYC | 5495 | 6435 | 7370 | 8190 | 9005 | 9710 | 10880 | 11700 |
| UPTO 15 CYC | 6555 | 7670 | 8785 | 9765 | 10740 | 11575 | 12970 | 13950 |
| UPTO 10 CYC | 7190 | 8415 | 9635 | 10710 | 11780 | 12695 | 14225 | 15300 |
| 10 HT | 4395 | 5145 | 5895 | 6550 | 7205 | 7765 | 8700 | 9360 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.