


AGRIMAX FORCE

| | |
|---------------------|--|
| TIRE SIZE | IF 650/75 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | SKÖRDEMASKIN / MOTORSTARK TRAKTOR / TRAKTOR |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 175 D |



DIMENSIONER IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 651 | RIM REC | DW 23 B |
| OD (MM) | 1941 | RIM ALT | DW 21 B |
| SLR (MM) | 866 | ECE | E11-106R-007385 |
| RC (MM) | 5802 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|----------------------|------|------|------|------|------|-------|-------|-------|
| 70 | 2955 | 3395 | 3895 | 4400 | 4900 | 5405 | 5905 | 6280 |
| FROM 65 TO 40 | 3245 | 3730 | 4280 | 4830 | 5385 | 5935 | 6490 | 6900 |
| 30 | 3375 | 3880 | 4455 | 5030 | 5605 | 6175 | 6750 | 7180 |
| 20 | 3505 | 4030 | 4625 | 5220 | 5815 | 6415 | 7010 | 7455 |
| 10 | 4120 | 4735 | 5435 | 6140 | 6840 | 7540 | 8240 | 8765 |
| UPTO 30 CYC | 4220 | 4845 | 5565 | 6280 | 7000 | 7715 | 8435 | 8970 |
| UPTO 15 CYC | 5030 | 5780 | 6635 | 7490 | 8345 | 9200 | 10055 | 10695 |
| UPTO 10 CYC | 5515 | 6335 | 7275 | 8215 | 9150 | 10090 | 11030 | 11730 |
| 10 HT | 3375 | 3880 | 4455 | 5030 | 5605 | 6175 | 6750 | 7180 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.